

SOT-23 Plastic-Encapsulate MOSFETS

P-Channel 30-V(D-S) MOSFET

FEATURE

TrenchFET Power MOSFET


APPLICATIONS

- Load Switch for Portable Devices
- DC/DC Converter

SO -23

1. GATE
2. SOURCE
3. DRAIN

MARKING: 2303



Maximum ratings ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current	I_D	-1.9	A
Continuous Source-Drain Diode Current	I_S	-0.83	
Maximum Power Dissipation	P_D	0.35	W
Thermal Resistance from Junction to Ambient($t \leq 5\text{s}$)	$R_{\theta JA}$	357	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-50 ~ +150	

Electrical characteristics ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Units	
Static							
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = -250\mu\text{A}$	-30			V	
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = -250\mu\text{A}$	-1		-3		
Gate-Source Leakage	I_{GSS}	$V_{\text{DS}} = 0\text{V}, V_{\text{GS}} = \pm 20\text{V}$			± 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = -30\text{V}, V_{\text{GS}} = 0\text{V}$			-1	μA	
Drain-Source On-State Resistance ^a	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = -10\text{V}, I_D = -1.9\text{A}$		0.158	0.190	Ω	
		$V_{\text{GS}} = -4.5\text{V}, I_D = -1.4\text{A}$		0.275	0.330		
Forward Transconductance ^a	g_{fs}	$V_{\text{DS}} = -5\text{V}, I_D = -1.9\text{A}$	1			S	
Dynamic^b							
Input Capacitance	C_{iss}	$V_{\text{DS}} = -15\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		155		pF	
Output Capacitance	C_{oss}			35			
Reverse Transfer Capacitance	C_{rss}			25			
Total Gate Charge	Q_g	$V_{\text{DS}} = -15\text{V}, V_{\text{GS}} = -10\text{V}, I_D = -1.9\text{A}$		4	8	nC	
Gate-Source Charge	Q_{gs}			2	4		
Gate-Drain Charge	Q_{gd}			0.6			
Gate Resistance	R_g		$f = 1\text{MHz}$	1.7	8.5	17	Ω
Turn-On Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = -15\text{V}, R_L = 10\Omega, I_D = -1.5\text{A}, V_{\text{GEN}} = -10\text{V}, R_g = 1\Omega$			4	8	ns
Rise Time	t_r				11	18	
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$				11	18	
Fall Time	t_f				8	16	
Turn-On Delay Time	$t_{\text{d}(\text{on})}$				36	44	
Rise Time	t_r	$V_{\text{DD}} = -15\text{V}, R_L = 10\Omega, I_D = -1.5\text{A}, V_{\text{GEN}} = -4.5\text{V}, R_g = 1\Omega$			37	45	
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$				12	18	
Fall Time	t_f				9	14	
Drain-source Body diode characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25^\circ\text{C}$			-1.75	A	
Pulse Diode Forward Current ^a	I_{SM}				-10		
Body Diode Voltage	V_{SD}	$I_S = -1.5\text{A}$		-0.8	-1.2	V	

Notes :

- a. Pulse Test : Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
b. Guaranteed by design, not subject to production testing.

Typical Characteristics

BC2303

