


## NPN Silicon Epitaxial Planar Transistor

High frequency amplifier application  
for FM IF, OSC stage and AM CONV. IF stage

The transistor is subdivided into three groups R, O, and Y, according to its DC current gain.



1.Base 2.Emitter 3.Collector  
SOT-23 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	35	V
Collector Emitter Voltage	$V_{CEO}$	30	V
Emitter Base Voltage	$V_{EBO}$	4	V
Collector Current	$I_C$	50	mA
Emitter Current	$-I_E$	50	mA
Power Dissipation	$P_{tot}$	200	mW
Junction Temperature	$T_j$	125	°C
Storage Temperature Range	$T_s$	-55 to +125	°C

### Characteristics at $T_{amb} = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 12 \text{ V}$ , $I_C = 2 \text{ mA}$	$R$	$h_{FE}$	40	-	80
	$O$	$h_{FE}$	70	-	140
	$Y$	$h_{FE}$	120	-	240
Collector Cutoff Current at $V_{CB} = 35 \text{ V}$	$I_{CBO}$	-	-	0.1	μA
Emitter Cutoff Current at $V_{EB} = 4 \text{ V}$	$I_{EBO}$	-	-	0.1	μA
Collector Emitter Saturation Voltage at $I_C = 10 \text{ mA}$ , $I_B = 1 \text{ mA}$	$V_{CE(sat)}$	-	-	0.4	V
Base Emitter Saturation Voltage at $I_C = 10 \text{ mA}$ , $I_B = 1 \text{ mA}$	$V_{BE(sat)}$	-	-	1	V
Transition Frequency at $V_{CE} = 10 \text{ V}$ , $I_C = 1 \text{ mA}$	$f_T$	100	-	400	MHz
Collector Output Capacitance at $V_{CB} = 10 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{ob}$	1.4	2	3.2	pF
Collector Base Time Constant at $V_{CE} = 10 \text{ V}$ , $-I_E = 1 \text{ mA}$ , $f = 30 \text{ MHz}$	$C_{c,r_{bb'}}$	10	-	50	ps
Power Gain at $V_{CC} = 6 \text{ V}$ , $f = 10.7 \text{ MHz}$ , $-I_E = 1 \text{ mA}$	$G_{pe}$	27	29	33	dB




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Base-Emitter Saturation Voltage  
Collector-Emitter Saturation Voltage




Figure 4. Base-Emitter On Voltage




Figure 5. Collector Output Capacitance






Figure 6. Current Gain Bandwidth Product

## PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

**SOT-23**



Symbol	Dimension in Millimeters	
	Min	Max
A	0.95	1.40
B	1.78	2.04
bp	0.35	0.50
C	0.08	0.19
D	2.70	3.10
E	1.20	1.65
HE	2.20	3.00
A1	0.100	0.013
Lp	0.20	0.50